



Form-in-Place Material

MP-L6x

Silver coated Aluminium Particles in Silicone Elastomer

Product Overview

UVOX MP-L6x is a material for electrically conductive Form-in-Place Gaskets. This material is suited for a combined environmental seal and RFI shield gasket. It can be applied directly onto parts which are to be sealed. Our MP-L6x Gaskets have a strong adhesion on the base material, a low Volume Resistance, a large temperature range usage as well as a high elasticity. It also offers high conductivity and high corrosion resistance on untreated surfaces Al, Zn or Mg.

Properties

Technical Specification

Property	Value	Unit	Test Method
Elastomer	Silicone		
Conductive Filler	Ag/Al		
Corrosion Prevention	Yes		
Curing System	Air Humidity		
Components	Single		
Volume Resistivity	< 8	mΩcm	
Shielding Effectiveness 20 MHz to 10 GHz	80 - 110	dB	MIL-DTL-83528C Para 4.5.12
Hardness	55	Shore A	ASTM D2240
Density (Cured)	2.0	N/cm ³	ASTM D395
Compression Set	6%	%	EMI-PM 0002 Rev. B
Adhesion Strength	> 10	N/cm ²	
Deformation Strength	6.0	N/cm	
Temperature Range	-40 to +160	°C	
Handling Time	1	h	
Full Cure	24	h	

www.uvox.co.uk

Uvox Ltd, 14/3 Stanmore Industrial Estate, Bridgnorth, Shropshire, WV15 5HR UK

Tel: +44(0) 1746 769 369

Fax: +44(0) 1746 766 001

info@uvox.co.uk

We believe the information contained in this datasheet is accurate and representative of the product, however; it is the responsibility of the user to determine the suitability and safety of use in any application. Uvox Ltd has a policy of continual improvement of our products and services, and so reserves the right to change product specification without notice.

© Uvox Limited. All rights reserved.