




# Carbon Sheet - Reinforced

*Gasket material giving environmental protection and conductivity*

## Product Overview

Uvox CSR sheet consists of compressed graphite with a nickel-reinforcing layer. It is highly conductive, making it ideal as an EMC gasket. Available thicknesses range from 0.4mm to 2.0mm. The material is available in sheet or cut to shape. Mounting pressures should be in the range 4.5 to 7.0kg/sq.cm for optimum sealing. At the upper pressure, IP62 can be achieved. Uvox CSR is supplied in 250mm x 250mm square cut sheets.



## Applications

- Waveguide and connector gaskets
- Gaskets for cast or machined electronic units
- Combination of thermal transfer and grounding pad for power supplies

## Properties

### Shielding Effectiveness

Frequency	Typical Value (dB)
1 MHz	>125
10 MHz	>120
100 MHz	>130
400 MHz	>110
1 GHz	85

### Typical Properties

Property	Typical Value
Resistivity (Ω/cm)	< 0.01
Flammability – UL94	V2
Temperature Range (°C)	-200 to +500
Hardness, Shore A	85
Tensile Strength (MPa)	>40
Tear Strength (kN/m)	3.5
Available Thicknesses (mm)	0.4 to 2.0

## Ordering Information

**CSR-07-25x25** – EMC Conductive Carbon Sheet, Reinforced, 0.7 x 250 x 250mm

[www.uvox.co.uk](http://www.uvox.co.uk)

Uvox Ltd, Faraday Drive, Bridgnorth, Shropshire, WV15 5BA, UK

Tel: +44(0) 1746 769 369

[sales@uvox.co.uk](mailto:sales@uvox.co.uk)



We believe the information contained in this datasheet is accurate and representative of the product, however; it is the responsibility of the user to determine the suitability and safety of use in any application. Uvox Ltd has a policy of continual improvement of our products and services, and so reserves the right to change product specification without notice.

© Uvox Limited. All rights reserved.